



Main

| | |
|------------------------------|--|
| Device short name | MX |
| Product or component type | Voltage release |
| Device application | Control |
| Range compatibility | Compact NSX EasyPact CVS PowerPact Multistandard |
| Voltage release type | Shunt trip release |
| [Uc] control circuit voltage | 208...277 V AC 60 Hz 220...240 V AC 50/60 Hz |

Complementary

| | |
|-------------------------------|--|
| Control signal type | Impulse Maintained |
| Impulse duration | ≥ 20 ms |
| Threshold tripping voltage | 0.7...1.1 x U_n opening |
| Supply inrush power | 10 VA |
| Mounting mode | Fixed |
| Response time | 50 ms |
| Auxiliary connection terminal | Screw terminal 0...1.5 mm ² |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |

| | |
|--------------------------|---|
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
