

# Product data sheet

Specifications



## Circuit breaker, ComPact NSX100F, 36kA/415VAC, TMD trip unit 80A, 4 poles 4d

LV429651

**!** To be discontinued on: 30 June 2023

**!** To be discontinued

**Important message :** This product has been switched to new ComPact range and is no longer commercialized. It will continue to be available in H1 2023 only limited to specific projects.

### Main

Range	ComPact
Product name	ComPact NSX
Range of product	ComPact NSX100...250
Device short name	NSX100F
Product or component type	Circuit breaker
Device application	Distribution
Number of poles	4P
Protected poles description	4t
Neutral position	Left
[In] rated current	80 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	10 kA at 600 V AC 50/60 Hz conforming to UL 508 25 kA at 480 V AC 50/60 Hz conforming to UL 508 85 kA at 240 V AC 50/60 Hz conforming to UL 508 22 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 25 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 35 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 36 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 8 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 85 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2
Performance level	F 36 kA 415 V AC
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Control type	Toggle
Circuit breaker mounting mode	Fixed

## Complementary

<b>[Ui] rated insulation voltage</b>	800 V AC 50/60 Hz
<b>[Uimp] rated impulse withstand voltage</b>	8 kV
<b>[Ics] rated service short-circuit breaking capacity</b>	11 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 35 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 36 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 4 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 85 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 12.5 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2
<b>Mechanical durability</b>	50000 cycles
<b>Electrical durability</b>	10000 cycles at 690 V In 20000 cycles at 690 V In/2 30000 cycles at 440 V In 50000 cycles at 440 V In/2
<b>Mounting support</b>	Backplate
<b>Upside connection</b>	Front
<b>Downside connection</b>	Front
<b>Connection pitch</b>	35 mm
<b>Protection type</b>	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
<b>Trip unit rating</b>	80 A at 40 °C
<b>Long-time pick-up adjustment type Ir (thermal protection)</b>	Adjustable
<b>[Ir] long-time protection pick-up adjustment range</b>	0.7...1 x In
<b>Long-time protection delay adjustment type tr</b>	Fixed
<b>[Tr] long-time protection delay adjustment range</b>	120...400 s at 1.5 x In 15 s at 6 x Ir
<b>Short-time protection pick-up adjustment type Isd</b>	Fixed
<b>[Isd] Short-time protection pick-up adjustment range</b>	640 A
<b>Short-time protection delay adjustment type tsd</b>	Fixed
<b>Earth-leakage protection</b>	Without
<b>Neutral protection settings</b>	1 x Ir (4t)
<b>Number of slots for electrical auxiliaries</b>	5 slot(s)
<b>Width (W)</b>	140 mm
<b>Height (H)</b>	161 mm
<b>Depth (D)</b>	86 mm
<b>Net weight</b>	2.4 kg
<b>Environment</b>	
<b>Standards</b>	EN/IEC 60947
<b>Product certifications</b>	CCC EAC Marine
<b>Overvoltage category</b>	Class II
<b>Electrical shock protection class</b>	Class II

<b>Pollution degree</b>	3 conforming to IEC 60664-1
<b>IP degree of protection</b>	IP40 conforming to IEC 60529
<b>IK degree of protection</b>	IK07 conforming to IEC 62262
<b>Ambient air temperature for operation</b>	-25...70 °C
<b>Ambient air temperature for storage</b>	-50...85 °C
<b>Relative humidity</b>	0...95 %
<b>Operating altitude</b>	0...2000 m without derating 2000 m...5000 m with derating

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	14.4 cm
<b>Package 1 Width</b>	14.9 cm
<b>Package 1 Length</b>	19.2 cm
<b>Package 1 Weight</b>	2.315 kg
<b>Unit Type of Package 2</b>	S04
<b>Number of Units in Package 2</b>	9
<b>Package 2 Height</b>	30.0 cm
<b>Package 2 Width</b>	40.0 cm
<b>Package 2 Length</b>	60.0 cm
<b>Package 2 Weight</b>	21.601 kg

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>RoHS exemption information</b>	Yes
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>California proposition 65</b>	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Recommended replacement(s)

LV429651 is replaced by:

---

1x



Circuit breaker, ComPact NSX100F, 36kA/415VAC, 4 poles 4D (neutral fully protected), TMD trip unit 80A

C10F4TM080

---