

# Product data sheet

Specifications



## Auxiliary contact, TeSys GV4, 690VAC, 1 NO/NC

GV4AE11

**Product availability:** Stock - Normally stocked in distribution facility

**Price\*:** 50.00 USD

### Main

Range	TeSys
Device Short Name	GV4AE
Product Or Component Type	Auxiliary contact
Device Application	Signalling
Range Compatibility	TeSys TeSys GV4 TeSys TeSys BV4
Auxiliary Contact Composition	1 NO/NC
[Ue] Rated Operational Voltage	<= 690 V
[Ith] Conventional Free Air Thermal Current	5 A IEC 60947-5-1 5 A CSA C22.2 No 14 5 A UL 508
Mounting Mode	Internal mounting

### Complementary

[Ui] Rated Insulation Voltage	690 V IEC 60947-1
[Ie] Rated Operational Current	5 A <= 690 V AC-12 IEC 60947-5-1 5 A <= 48 V AC-15 IEC 60947-5-1 4 A 110/127 V AC-15 IEC 60947-5-1 3 A 220/240 V AC-15 IEC 60947-5-1 2.5 A 380...440 V AC-15 IEC 60947-5-1 0.11 A 660/690 V AC-15 IEC 60947-5-1 5 A <= 24 V DC-12 IEC 60947-5-1 2.5 A 48 V DC-12 IEC 60947-5-1 0.6 A 110/127 V DC-12 IEC 60947-5-1 0.3 A 250 V DC-12 IEC 60947-5-1 2.5 A <= 24 V DC-12 IEC 60947-5-1 1.2 A 48 V DC-12 IEC 60947-5-1 0.35 A 110/127 V DC-12 IEC 60947-5-1 0.05 A 250 V DC-12 IEC 60947-5-1 1 A <= 24 V DC-12 IEC 60947-5-1 0.2 A 48 V DC-12 IEC 60947-5-1 0.05 A 110/127 V DC-12 IEC 60947-5-1 0.03 A 250 V DC-12 IEC 60947-5-1
Rated Power In Va	120 VA AC-12 24 V IEC 60947-5-1 240 VA AC-12 48 V IEC 60947-5-1 635 VA AC-12 110/127 V IEC 60947-5-1 1200 VA AC-12 230/240 V IEC 60947-5-1 2200 VA AC-12 380/440 V IEC 60947-5-1 3450 VA AC-12 660/690 V IEC 60947-5-1
Rated Power In W	DC-12 120 W 24 V IEC 60947-5-1 DC-12 120 W 48 V IEC 60947-5-1 DC-12 66 W 110 V IEC 60947-5-1 DC-12 75 W 250 V IEC 60947-5-1
Associated Fuse Rating	5 A gG at 690 V conforming to IEC 60947-5-1
Minimum Switching Current	2 mA

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Minimum Switching Voltage</b>	17 V
<b>Mechanical Durability</b>	40000 cycles
<b>Connections - Terminals</b>	Spring terminals 1 0.00...0.00 in <sup>2</sup> (0.5...1.5 mm <sup>2</sup> ) - cable stiffness: flexible without cable end
<b>Wire Stripping Length</b>	0.31 in (8 mm)

## Environment

<b>Quantity Per Set</b>	Set of 1
-------------------------	----------

## Ordering and shipping details

<b>Category</b>	22366-MAN STR PROTECTORS-GV1/GV3
<b>Discount Schedule</b>	I11
<b>Gtin</b>	3606485444246
<b>Returnability</b>	Yes
<b>Country Of Origin</b>	CN

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	0.79 in (2.000 cm)
<b>Package 1 Width</b>	3.15 in (8.000 cm)
<b>Package 1 Length</b>	4.33 in (11.000 cm)
<b>Package 1 Weight</b>	0.85 oz (24.000 g)
<b>Unit Type Of Package 2</b>	BB1
<b>Number Of Units In Package 2</b>	10
<b>Package 2 Height</b>	1.57 in (4.000 cm)
<b>Package 2 Width</b>	6.30 in (16.000 cm)
<b>Package 2 Length</b>	10.63 in (27.000 cm)
<b>Package 2 Weight</b>	8.85 oz (251.000 g)
<b>Unit Type Of Package 3</b>	S03
<b>Number Of Units In Package 3</b>	220
<b>Package 3 Height</b>	11.81 in (30 cm)
<b>Package 3 Width</b>	11.81 in (30 cm)
<b>Package 3 Length</b>	15.75 in (40 cm)
<b>Package 3 Weight</b>	14.01 lb(US) (6.353 kg)

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Compliant

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Weee**

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

**Circularity Profile**

[End of Life Information](#)

**California Proposition 65**

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)